



Mitsubishi (EU)
Pajero / Shogun / Montero
Pajero / Shogun 2.5 TD (1991 - 2001)

Drive type	a.w.d.
Fuel	Diesel
Engine build	Line
Cylinders	4
Valves per cylinder	2
Displacement	2477 cc
Power rating	99 HP / 73 kW

Engine 4D56

Capacities:	Capacity 6,7 litre Filter capacity 0,8 litre
Use condition:	Normal
Interval:	Change 7500 km/ 6 months
Recommendation:	(Above -15°C) MaxLife Motor Oil 15W-40 (High Mileage) (Above -15°C) All Climate 15W-40 (Above -10°C) All Climate 20W-50 (Above -10°C) VR1 Racing Oil 20W-50

Transmission, manual 5/1

Capacity:	Capacity 2,5 litre
Use condition:	Normal
Intervals:	Check 15000 km/ 12 months
Intervals:	Change 45000 km/ 36 months
Recommendation:	(year-round) Valvoline Gear Oil 75W-90 (year-round) Valvoline Gear Oil 75W-80 (year-round) Valvoline TDL 75W-90

Transmission, automatic 4/1

Capacity:	Capacity 7,5 litre
Use condition:	Normal
Intervals:	Check 15000 km/ 12 months
Intervals:	Change 45000 km/ 36 months
Recommendation:	(year-round) Valvoline ATF(Volvo,Mazda,PSA,6-sp.,<2010,call technical)

Transferbox

Capacity:	Capacity 2,3 litre
Use condition:	Normal
Intervals:	Check 15000 km/ 12 months
Intervals:	Change 45000 km/ 36 months
Recommendation:	(year-round) Valvoline Gear Oil 75W-90 (year-round) Valvoline Gear Oil 75W-80 (year-round) Valvoline TDL 75W-90

Differential, front

Capacity:	Capacity 1,2 litre
Use condition:	Normal
Intervals:	Check 30000 km/ 24 months
Intervals:	Change 90000 km/ 72 months
Recommendation:	(year-round) Valvoline Light & Heavy Duty Axle Oil 80W-90

Differential, rear

Capacity:	Capacity 1,8 litre
Use condition:	Normal
Intervals:	Check 30000 km/ 24 months
Intervals:	Change 90000 km/ 72 months
Recommendation:	(year-round) Valvoline Light & Heavy Duty Axle Oil 80W-90
Use condition:	severe
Intervals:	Check 15000 km/ 12 months
Intervals:	Change 45000 km/ 36 months
Recommendation:	(year-round) Valvoline Light & Heavy Duty Axle Oil 80W-90

Differential, rear, limited slip

Capacity:	Capacity 1,8 litre
------------------	--------------------

Use condition: Normal
Intervals: Check 30000 km/ 24 months
Intervals: Change 45000 km/ 36 months
Recommendation: (year-round) Heavy Duty Axle Oil Pro 80W-90 LS
Use condition: severe
Interval: Change 30000 km/ 24 months
Recommendation: (year-round) Heavy Duty Axle Oil Pro 80W-90 LS

Differential, rear, with differential lock

Capacity: Capacity 2,6 litre
Use condition: Normal
Intervals: Check 30000 km/ 24 months
Intervals: Change 90000 km/ 72 months
Recommendation: (year-round) Valvoline Light & Heavy Duty Axle Oil 80W-90
Use condition: severe
Intervals: Check 15000 km/ 12 months
Intervals: Change 45000 km/ 36 months
Recommendation: (year-round) Valvoline Light & Heavy Duty Axle Oil 80W-90

Hydraulic brake / clutch system

Use condition: Normal
Intervals: Check 15000 km/ 12 months
Intervals: Change 30000 km/ 24 months
Recommendation: (year-round) Brake & Clutch Fluid DOT 3

Power steering

Capacity: Capacity 1 litre
Use condition: Normal
Intervals: Check 15000 km/ 12 months
Intervals: Change 45000 km/ 36 months
Recommendation: (year-round) Valvoline ATF(Volvo,Mazda,PSA,6-sp.,<2010,call technical)

Grease points / nipples, wheel bearings

Use condition: Normal
Interval: Change 60000 km/ 48 months
Recommendation: (year-round) Multi Purpose Lithium EP 2
(year-round) Multi Purpose Complex Red 2
(year-round) Multi Purpose Complex Amber 2

Grease points / nipples, others

Use condition: Normal
Interval: Check 24 months/ 30000 km
Recommendation: (year-round) Multi Purpose Lithium EP 2
(year-round) Multi Purpose Complex Red 2
(year-round) Multi Purpose Complex Amber 2

Cooling system

Capacities: Capacity 9,5 litre
Capacity 10,5 litre + rear heater
Use condition: Normal
Intervals: Check 15000 km/ 12 months
Intervals: Change 60000 km/ 48 months
Recommendation: (year-round) Valvoline Zerex G40 RTU
(year-round) Valvoline ZEREX G48 Concentrate
(year-round) Multi-Vehicle Coolant RTU
(year-round) Multi-Vehicle Coolant Concentrate
(year-round) Multi-Vehicle Coolant Red RTU
(year-round) Multi-Vehicle Coolant Red Conc.

Steering box

Capacity: Capacity 0,21 litre
Use condition: Normal
Intervals: Check 15000 km/ 12 months
Intervals: Change 45000 km/ 36 months
Recommendation: (year-round) Valvoline Light & Heavy Duty Gear Oil 80W-90
(year-round) Valvoline Gear Oil 75W-80

