



Mitsubishi (EU)
Pajero / Shogun / Montero
Pajero / Shogun 2.5 TD (2001 - 2007)

Drive type	a.w.d.
Fuel	Diesel
Engine build	Line
Cylinders	4
Valves per cylinder	2
Displacement	2477 cc
Power rating	99 HP / 73 kW

Engine 4D56

Capacities:	Capacity 7,3 litre Filter capacity 0,8 litre
Use condition:	Normal
Interval:	Change 15000 km/ 12 months
Recommendation:	(Above -15°C) MaxLife Motor Oil 15W-40 (High Mileage) (Above -15°C) All Climate 15W-40 (Above -10°C) All Climate 20W-50 (Above -10°C) VR1 Racing Oil 20W-50
Use condition:	severe
Interval:	Change 7500 km
Recommendation:	(Above -15°C) MaxLife Motor Oil 15W-40 (High Mileage) (Above -15°C) All Climate 15W-40 (Above -10°C) All Climate 20W-50 (Above -10°C) VR1 Racing Oil 20W-50

Transmission, manual 5/1

Capacity:	Capacity 3,2 litre
Use condition:	Normal
Intervals:	Check 15000 km/ 12 months
Intervals:	Change 45000 km/ 36 months
Recommendation:	(year-round) Valvoline Gear Oil 75W-90 (year-round) Valvoline Gear Oil 75W-80 (year-round) Valvoline TDL 75W-90

Transferbox

Capacity:	Capacity 2,5 litre
Use condition:	Normal
Intervals:	Check 15000 km/ 12 months
Intervals:	Change 45000 km/ 36 months
Recommendation:	(year-round) Valvoline Gear Oil 75W-90 (year-round) Valvoline Gear Oil 75W-80 (year-round) Valvoline TDL 75W-90

Differential, rear, limited slip

Capacity:	Capacity 1,6 litre
Use condition:	Normal
Intervals:	Check 30000 km/ 24 months
Intervals:	Change 45000 km/ 36 months
Recommendation:	(year-round) Heavy Duty Axle Oil Pro 80W-90 LS

Differential, front

Capacity:	Capacity 1,15 litre
Use condition:	Normal
Intervals:	Check 30000 km/ 24 months
Intervals:	Change 90000 km/ 72 months
Recommendation:	(Above 10°C) Valvoline Light & Heavy Duty Axle Oil 80W-90

Differential, rear

Capacity:	Capacity 1,6 litre
Use condition:	Normal
Intervals:	Check 30000 km/ 24 months
Intervals:	Change 90000 km/ 72 months
Recommendation:	(Above 10°C) Valvoline Light & Heavy Duty Axle Oil 80W-90

Hydraulic brake / clutch system

Use condition:	Normal
Intervals:	Check 15000 km/ 12 months
Intervals:	Change 30000 km/ 24 months
Recommendation:	(year-round) Brake & Clutch Fluid DOT 3 (year-round) Brake & Clutch Fluid DOT 4

Power steering

Capacity:	Capacity 1 litre
Use condition:	Normal
Interval:	Check 12 months/ 30000 km
Recommendation:	(year-round) Valvoline ATF(Volvo,Mazda,PSA,6-sp.,<2010,call technical)

Cooling system

Capacities:	Capacity 9 litre Capacity 10,5 litre + airconditioning
Use condition:	Normal
Intervals:	Check 30000 km/ 24 months
Intervals:	Change 60000 km/ 48 months
Recommendation:	(year-round) Valvoline Zerex G40 RTU (year-round) Valvoline ZEREX G48 Concentrate (year-round) Multi-Vehicle Coolant RTU (year-round) Multi-Vehicle Coolant Concentrate (year-round) Multi-Vehicle Coolant Red RTU (year-round) Multi-Vehicle Coolant Red Conc.

© Olyslager 2020 All rights reserved. No part of this information may be reproduced, stored in any retrieval system, or transmitted in any form or by any means without any prior written permission from Olyslager Organisation B.V.. Although every care is taken to ensure accuracy and completeness in compiling these data, no liability, other than that which may not be excluded by law, can be accepted for damage or loss caused by any errors or omissions in the information given. By accessing and using this oil recommendation information, the user confirms that he/she has the experience, the knowledge and the ability to perform the required maintenance activity in a safe and responsible manner. He/she also holds harmless and indemnifies the publisher against any loss, injury, claim and penalties arising from the wrongful interpretation or incorrect usage of the published information. Data release: LIS 2019 Q4